

GASEOUS FUEL DISCHARGING STRUCTURE FOR VEHICLE

FIELD OF THE INVENTION

[0001] The present invention relates to a gaseous fuel
5 discharging structure for use with a gaseous fuel containing tank
disposed within a trunk of a vehicle, and in particular to the
structure which, if gaseous fuel unfortunately leaks from within
the tank, directs such gaseous fuel out of the trunk.

BACKGROUND OF THE INVENTION

10 [0002] Gaseous fuel discharging structures for vehicles are
well known in the art. One example of such structures is known
from Japanese Patent Laid-Open Publication No. HEI-8-99544
entitled "STRUCTURE FOR AUTOMOBILE HAVING MOUNTED THERETO END
OF PIPE FOR DISCHARGING LEAKAGE COMPRESSED GASEOUS FUEL". The
15 publication discloses an automobile having gaseous fuel
containing tanks mounted within a trunk thereof. The tanks are
connected to plural exits of a gas supply pipe. The gas supply
pipes have one entrance provided in fluid communication with a
filler formed in a recess positioned at a rear side wall portion
20 of an automobile body.

[0003] The recess is covered with a cover. With the cover
opened, the tanks can be filled with gaseous fuel supplied from
the gas supply pipe.

[0004] The recess also has formed therein an opening which
25 is in fluid communication with one discharge port of a gas discharge
pipe. The gas discharge pipe has plural intake ports each
connected to a junction at which each exit of the gas supply pipe

is connected to the tank. Even if gaseous fuel undesirably leaks from within the tanks, such leaked gas flows into the intake ports of the gas discharge pipe out of the discharge port.

5 [0005] Since the recess is formed at the rear wall portion of the automobile body, the former is small in size to provide pleasant appearance of the automobile. This requires the gas supply pipe to have a limited diameter.

10 [0006] For the gas discharging structure disclosed in the publication, gaseous fuel leaked from within the tanks spontaneously flows through the gas discharge pipe out of the automobile body. In other words, such leaked gaseous fuel is slowly discharged into the open air. What has been needed is a structure for advantageously discharging the gaseous fuel into the open air.

15 [0007] Fuel-cell-powered automobiles typically employ hydrogen gas as gaseous fuel. For resinous tanks holding such hydrogen gas therein, the hydrogen gas could undesirably pass through the tank.

20 [0008] Especially for the fuel-cell-powered automobiles, therefore, there is required a structure for advantageously discharging into the open air the hydrogen gas leaked the tanks.

SUMMARY OF THE INVENTION

25 [0009] An object of the present invention is to provide a gaseous fuel discharging structure for a vehicle, which rapidly discharges gaseous fuel, leaked from within a fuel tank, into the air.

[0010] According to an aspect of the present invention, there is provided a gaseous fuel discharging structure for a vehicle

having a trunk and a gaseous fuel containing tank disposed in a hermetic space defined within the trunk, which gaseous fuel discharging structure comprises: an air introducing pipe communicating with the hermetic space and extending to outside of the vehicle; a gas discharging pipe communicating with the hermetic space and extending to the outside of the vehicle; forced ventilation means disposed on at least one of the air introducing pipe and the gas discharging pipe for forcedly ventilating the hermetic space; and an opening/closing device disposed on each of the air introducing pipe and the gas discharging pipe, the opening/closing devices being held at a closed position to seal the air introducing pipe and the gas discharging pipe when the forced ventilation means is out of operation and, when the forced ventilation means is in operation, pivoted to an opened position so that any gaseous fuel leaked from the gaseous fuel containing tank into the hermetic space is forced out of the vehicle through the gas discharging pipe by fresh air flowing through the air introducing pipe into the hermetic space.

[0011] At least one of the air introducing pipe and the gas discharging pipe has a forced ventilating device. Each of the air introducing pipe and the gas discharging pipe includes the opening/closing device. Operation of the forced ventilating device causes the opening/closing device of the air introducing pipe to be opened so that air outside the vehicle is drawn through the air introducing pipe into the cover. Such air is discharged out of the gas discharging pipe along with the gaseous fuel leaked from the tank.

[0012] By thus driving the forced ventilating device in such a manner that the air outside the vehicle is forcibly taken into the cover, the gaseous fuel which remains within the cover after leaked from within the tank is rapidly discharged out of the vehicle along with the air. Accordingly, it becomes possible to efficiently ventilate a space formed within the cover.

[0013] As the forced ventilating device is out of operation, the opening/closing devices are held in the closed positions. Since these opening/closing devices normally close the air introducing pipe and the gas discharging pipe, noise is no longer transmitted through these pipes into a passenger compartment of the vehicle. Moreover, unwanted foreign materials such as water and dust are prevented from entering into the air introducing pipe and the gas discharging pipe.

[0014] In a preferred form of the present invention, the hermetic space is defined by a sealing cover hermetically enclosing the gaseous fuel containing tank, and the air introducing pipe and the gas discharging pipe extend outwardly of the vehicle from the sealing cover. The forced ventilation means may comprise a fan to be actuated upon leakage of the gaseous fuel. The opening/closing devices may comprise flaps to be pivoted to the opened position by the flow of air produced by the fan.

[0015] Desirably, the gas discharging structure further comprises a floor plate provided for carrying an entrance of the air introducing pipe and an exit of the gas discharging pipe thereon. The floor plate may have right and left side frames mounted thereon. One of the entrance and the exit may be positioned outwardly of

the left side frame while the other of the entrance and the exit may be positioned outwardly of the right side frame.

[0016] The entrance of the air introducing pipe and the exit of the gas discharging pipe are provided at the floor plate. These
5 pipes are difficult to view from outside the vehicle.

[0017] One of the air introducing pipe and the gas discharging pipe is provided externally of the left side frame while the other is provided externally of the right side frame. This arrangement has the advantage that the mixture discharged out of exit of the
10 gas discharging pipe is not drawn into the entrance of the air introducing pipe.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] A certain preferred embodiment of the present invention will hereinafter be described in detail, by way of example only,
15 with reference to the accompanying drawings, in which:

[0019] Fig. 1 is a side elevation view of a rear part of a gaseous fuel-powered automobile including a gaseous fuel discharging structure according to the present invention;

[0020] Fig. 2 is a cross-sectional view taken along line 2-2
20 of Fig. 1;

[0021] Fig. 3 is a cross-sectional view taken along line 3-3 of Fig. 2;

[0022] Fig. 4 is a cross-sectional view taken along line 4-4 of Fig. 2;

25 [0023] Figs. 5A and 5B are views illustrating how a spontaneous ventilation structure is operated when gaseous fuel leaks from within a gaseous fuel containing tank;

[0024] Fig. 6A is a view showing how a forced ventilation structure is operated when gaseous fuel is leaked in large amount from within the tank and Fig. 6B is a view showing how the forced ventilation structure draws air from outside the automobile thereinto;

[0025] Fig. 7A is a view illustrating the flow of the air into the forced ventilation structure and Fig. 7B is a view showing the flow of mixture of the air and the gaseous fuel through the forced ventilation structure;

[0026] Figs. 8A and 8B are views illustrating the flow of the mixture out of the forced ventilation structure; and

[0027] Fig. 9 is a view showing how the forced ventilation structure discharges the gaseous fuel out of the automobile.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0028] Referring to Fig. 1, a gaseous fuel-powered automobile includes an automobile body 11 having rear pillars 13 (only one shown) positioned at a rear part 12 thereof. The rear pillars 13 have a roof 15 mounted at a top 14 thereof. The roof 15 has its rear end 16 disposed in opposed relation to an upper frame member 21 with a given interval (a gap 22 formed between the roof 15 and the tailgate 20) formed therebetween. A tailgate 20 is mounted at the rear part 12 in such a manner as to pivot in an up-and-down direction. The rear part 12 has a trunk 17 formed therein. An airtight or sealing cover 30 is disposed within the trunk 17 and on a bottom of the rear part 12 by means of a bracket 31. The cover 30 covers a gaseous fuel containing tank 40. The cover 30 is provided with a spontaneous ventilation structure

50 and a forced ventilation structure 60 (a gaseous fuel discharging structure). The spontaneous ventilation structure 50 is arranged such that gaseous fuel leaked from within the tank 40 spontaneously flows out of the automobile body 11. The forced discharge is arranged such that gaseous fuel leaked from within the tank 40 is forced to flow out of the automobile body 11.

[0029] Gaseous fuel the automobile 10 employs is natural gas or hydrogen gas, for example. The tank 40 as used herein is made of resin. It is noted that the tank 40 may be also formed of any material other than resin.

[0030] Reference numerals 25, 26, 27, 28, 29 denote a rear wheel, a rear bumper, a glass window mounted on the tailgate 20, a rear side glass window, and a rear seat, respectively.

[0031] Turning to Fig. 2, the automobile body 11 includes a floor plate 33. Attached to an underside of the floor plate 33 are right and left side frames 47, 46 spaced from each other by a given interval.

[0032] The airtight cover 30 is mounted to the floor plate 33 via right and left channel portions 32b, 32a. The tank 40 is housed or encased in the cover 30. A bottom 34 of the cover 30 has right and left air introducing pipes 36, 35 mounted at right and left ends 34b, 34a thereof, respectively. The cover 30 has right and left communication pipes 38b, 38a provided at right and left top ends 37b, 37a thereof.

[0033] These communication pipes 38b, 38a are connected to the spontaneous ventilation structure 50.

[0034] The tank 40 has two bands 42, 42 wound thereon. By means

of the bands 42, 42, the tank 40 is mounted to a support bracket (not shown) of the automobile body 11. A gas filling pipe 44 and a gas supply pipe (not shown) are connected to a left end 43 of the tank 40. The gas filling pipe 44 is used to fill the tank 40 with gaseous fuel whilst the gas supply pipe is used to supply an engine (not shown) with gaseous fuel contained within the tank 40.

[0035] The left air introducing pipe 35 has a communication pipe 38c connected to a lower end 35a thereof while the right air introducing pipe 36 has a communication pipe 38d connected to a lower end 36a thereof. The communication pipes 38c, 38d has their exits exposed to the open air. The communication pipes 38c, 38d have their opened upper ends 35b, 36b positioned within the cover 30. Air outside the automobile body 11 is introduced into the cover 30 through the pipe 35, 36.

[0036] The spontaneous ventilation structure 50 includes a left gas spontaneous discharger 51 provided to the left communication pipe 38a, and a right gas spontaneous discharger 52 provided to the right communication pipe 38b.

[0037] The right and left gas spontaneous dischargers 52, 51 are identical in structure with each other, and hence the description of the left gas spontaneous discharger 51 is omitted.

[0038] The right gas spontaneous discharger 52 includes a discharge pipe 54 for directing gaseous fuel, which leaked from within the tank 40, out of the automobile body 11. Positioned a given interval away from a discharge port 57 of the discharge pipe 54 is a water entry preventing member 58 for preventing water

such as rainwater from entering into the discharge pipe 54. The discharge pipe 54 has an additional water drainage pipe 59 attached thereto. If water enters into the discharge pipe 54, the former flows through the water drainage pipe 59 out of the automobile body 11.

[0039] Providing the water entry preventing member 58 makes it possible to prevent rainwater and the like from entering into the discharge pipe 54 through the discharge port 57.

[0040] The discharge pipe 54 includes a first discharge pipe 55a connected to the right communication pipe 38b, a connection block 56 having a side communication pipe 56a connected to the first discharge pipe 55a, and a second discharge pipe 55b through which the discharge port 57 communicates with an upper communication pipe 56b of the connection block 56.

[0041] The discharge port 57 is positioned within a space 23 below the gap 22.

[0042] The second discharge pipe 55b is oriented substantially vertically to allow gaseous fuel leaked from within the tank 40 to spontaneously flow through the first discharge pipe 55a, the connection block 56, and the second discharge pipe 55b out of the automobile body 11.

[0043] The connection block 56 has its lower connection member 56c connected to an entrance 59a of the water drainage pipe 59. The water drainage pipe 59 extends downwardly and has an exit 59b positioned outside the automobile body 11. With this arrangement, even if water unfortunately enters the discharge pipe 54, the former is unlikely to remain within the discharge

pipe 54.

[0044] The forced ventilation structure 60 includes an air introducer 61 for forcibly introducing air outside the automobile body 11 into the cover 30, a gas discharger 62 for discharging
5 out of the automobile body 11 a mixture of gaseous fuel leaked from within the tank 40 and the air introduced through the air introducer 61 into the cover 30, and a gas detector 90 for detecting gaseous fuel which is leaked from within the tank 40 and remains within the cover 30.

[0045] The air introducer 61 includes an air introducing pipe.
10 64. The pipe 64 has its top end (exit) 64a connected to an upper portion 39a of a left side wall of the airtight cover 30. A bottom end (entrance) 64b of the pipe 64 has a rubber-made intake flap 70 mounted therewithin. The flap 70 is pivotable between a closed
15 position and an opened position. The bottom end 64b also has a fan 75 mounted therewithin. The fan 75 is positioned above the flap 70.

[0046] Operation of the fan 75 causes the flap 70 to pivot to the opened position in which air outside the automobile body
20 11 is taken into the cover 30.

[0047] The gas discharger 62 includes a gas discharging pipe 80. The pipe 80 has its top end (entrance) 80a connected to an upper portion 39b of a right side wall of the cover 30. A bottom end (exit) 80b of the pipe 80 has a rubber-made discharge flap
25 86 mounted therewithin. The discharge flap 86 is pivotable between a closed position and an opened position.

[0048] As the fan 75 of the air introducer 61 is operated to

take air outside the automobile body 11 into the air introducer 61, the flap 86 is caused to pivot to the opened position as will be discussed in detail. With the flap 86 in the opened position, a mixture of the introduced air and the leaked gaseous fuel is allowed to flow out of the automobile body 11.

[0049] The entrance 64b and the exit 80b are provided at the floor plate 33. More specifically, the entrance 64b of the gas discharging pipe 80 is provided outside the left side frame 46 and above a lower surface 46a of the left side frame 46. Likewise, the exit 80b of the gas discharge pipe 80 is provided outside the right side frame 47 and above a lower surface 47a of the right side frame 47.

[0050] The side frames 46, 47 are positioned between the entrance 64b and the exit 80b. With this arrangement, it is unlikely that gaseous fuel discharged out of the exit 80b is drawn into the entrance 64b. It thus becomes possible to efficiently ventilate a hermetic or sealed space 30a defined within the airtight cover 30.

[0051] The gas detector 90 includes a gas sensor 91 attached to the left top end 37a of the cover 30, and a control unit 92 for driving the fan 75 on the basis of a signal sent from the gas sensor 91.

[0052] When an amount of gaseous fuel which is leaked from within the tank 40 and remains within the space 30a exceeds a threshold level, the gas sensor 91 is operated to detect the presence of such gaseous fuel and supply the control unit 92 with a detection signal indicative of the detection of the gaseous

fuel. The control unit 92 sends a motor 76 of the fan 75 a drive signal for driving the motor 76. Upon receiving the drive signal, the motor 76 is driven to rotate blades 78 attached thereto.

[0053] When the amount of the gaseous fuel remaining within the cover 30a is made less than the threshold level, the gas sensor 91 stops its operation of detecting the gaseous fuel. In other words, the gas sensor 91 sends no detection signals to the control unit 92. Therefore, the fan 75 is supplied with no drive signals. The blades 78 consequently stop rotating.

[0054] The gas detector 90 as used herein is arranged such that the control unit 92 controls the fan 75. The gas detector 90 may be applicable to a vehicle having an indication part and an operation button both provided proximate a driver's seat. In this case, when the gas sensor 91 detects the gaseous fuel having an amount greater than the threshold level, the indication part is lit up to thereby indicate to a driver that the gaseous fuel is leaked from within the tank 40. The driver pushes the operation button to thereby drive the motor 76 of the fan 75 in the manner as stated above.

[0055] With respect to Fig. 3, the entrance 64b includes a taper portion 65a, a first enlarged pipe portion 65b communicating with the taper portion 65a, and a second enlarged pipe portion 65c communicating with the first enlarged pipe portion 65b. The second enlarged pipe portion 65c is mounted to the floor plate 33.

[0056] The entrance 64b provided above the floor plate 33 is difficult to view from outside the automobile body 11 to thereby

provide a pleasant appearance of the automobile body 11.

[0057] Within the second enlarged pipe portion 65c, there is formed an intake portion 67 having a flange 68 mounted at a left opening portion 33a of the floor plate 33. The flap 70 is mounted
5 on the flange 68 in such a manner as to pivot on a pin 59.

[0058] The intake flap 70 has the pin 59 provided rightwardly thereof. This arrangement is advantageous in that as the fan 75 is out of operation, the flap 70 remains horizontally oriented abutting on a projection portion 68a under its own weight to thereby
10 keep an opening 68b closed. As the fan 75 is operated, the flap 70 is pivoted clockwise under a wind pressure produced by the operation of the fan 75 to thereby open the opening 68b.

[0059] The flap 70 as used herein is pivotable on the pin 59. Utilizing the flexibility of the rubber-made flap 70, however,
15 the flap 70 may be mounted to the flange 68 without using the pin 59. In such a case, as the fan 75 is operated, the flap 70 can be bent or flexed upwardly under a wind pressure produced by the operation of the fan 75 to thereby open the opening 68b. As the fan 75 is out of operation, the flap 70 remained oriented
20 horizontally, abutting on the projection portion 68a under its own weight to thereby keep the opening 68b closed, as discussed above.

[0060] Beneath the flange 68, there is formed an intake pipe 72 bent into a substantially L-shaped configuration. The intake
25 pipe 72 extends backwardly and is positioned outside the automobile body 11. Mounted on the flange 68 is a guide cylinder 73 extending towards the fan 75.

[0061] The motor 76 is mounted via plural stays 77 to the taper portion 65a. The blades 78 are rotationally positioned within the first enlarged pipe portion 65b.

[0062] As the flap 70 is kept closed under its own weight,
5 the air introducing pipe 64 is usually closed. With the pipe 64 closed, noise is prevented from being transmitted through the pipe 64 into a passenger compartment of the automobile 10. In addition, it becomes possible to prevent unwanted foreign materials such as water and dust from entering into the pipe 64.

10 [0063] The intake flap 70 is protected by a lower wall surface 72a of the L-shaped intake pipe 72. More specifically, the lower wall surface 72a serves to prevent foreign materials over a road from entering into the intake pipe 72 and striking the flap 70. The intake flap 70 is thus no longer damaged.

15 [0064] Referring to Fig. 4, an exit 80b of the gas discharging pipe 80 includes a taper portion 81a, and an enlarged pipe portion 81b communicating with the taper portion 81a. The enlarged pipe portion 81b has a mounting wall 81c extending inwardly therefrom. The mounting wall 81c is directed perpendicularly to the enlarged
20 pipe portion 81b.

[0065] The enlarged pipe portion 81b has one lower end 82a mounted on the floor plate 33. Another end 82b of the enlarged pipe portion 81b is attached to a flange 84 of a discharge part 83. The flange 84 is attached to a mounting wall 33c mounted
25 on the floor plate 33. The enlarged pipe portion 81b communicates with a right opening portion 33b of the floor plate 33. The right opening portion 33b communicates with the outside of the

automobile body 11.

[0066] Because the exit 80b is provided above the floor plate 33, the former is difficult to view from outside the automobile body 11 to thereby provide a pleasant appearance of the automobile

5 10.

[0067] The discharge part 83 is disposed within the enlarged pipe portion 81b. The flange 84 of the discharge part 83 is mounted to the mounting walls 33c, 81c. A discharge flap 86 is mounted to the flange 84 in such a manner as to pivot on a pin 85.

10 [0068] The pin 85 is positioned at a higher level than the discharge flap 86. This arrangement provides the advantage that as the fan 75 is out of operation, the flap 86 usually remains oriented substantially vertically under its own weight, abutting on a projection portion 84a of the flange 84 to thereby keep an opening 84b closed. As the fan 75 is operated, the flap 86 can be pivoted counterclockwise to open the opening 84b, as will be discussed later in detail.

[0069] The discharge part 83 has a substantially L-shaped guide cylinder 88 positioned forwardly of the flange 84. The guide cylinder 88 has its entrance 88a oriented towards the gas discharging pipe 80. A discharge port portion 89 extends backwardly from the flange 84.

20 [0070] In the illustrated embodiment, the flap 86 is pivotable on the pin 85. Utilizing the flexibility of the rubber-made flap 86, however, the flap 86 may be mounted to the flange 84 without using the pin 85. In such a case, the flap 86 is bent or flexed rightwardly to open the opening 84b. It is to be understood that

as the fan 75 is out of operation, the flap 86 mounted to the flange 84 without using the pin 85 also is usually oriented substantially vertically, abutting on the projection portion 84a under its own weight to thereby keep the opening 84b closed.

5 [0071] Since the flap 86 usually closes the opening 84b, noise is prevented from passing through the gas discharging pipe 80 into the passenger compartment of the automobile 10. Moreover, foreign materials such as water and dust no longer enter into the pipe 80.

10 [0072] A lower wall surface 89a of the horizontally extending discharge port portion 89 is provided for protecting the discharge flap 86 from undesirable foreign materials over the road. More specifically, such foreign materials are prevented from striking the flap 86. The flap 86 can not be damaged, accordingly.

15 [0073] Reference is made to Fig. 5A illustrating the spontaneous ventilation structure 50 with the forced ventilation structure omitted for explanatory purpose.

[0074] If gaseous fuel is leaked out of a connection point at which the gas filling pipe 44 and the gas supply pipe (not shown) are connected to the tank 40, the former remains within the space 30a.

[0075] Air outside the automobile body 11 is introduced into the space 30a through the air introducing pipes 35, 36, as shown by arrows ①, ①.

25 [0076] At this point, the amount of gaseous fuel thus remaining within the space 30a does not yet exceed the threshold level, and therefore the intake flap 70 is held in the closed position

as shown in Fig. 3.

[0077] The gaseous fuel within the space 30a spontaneously enters into the second discharge pipes 55b, 55b via the first discharge pipes 55a, 55a and the connection blocks 56, 56, as indicated by arrows ②, ②, ③, ③.

[0078] The gaseous fuel flows out of the discharge ports 57, 57, as shown by arrows ④, ④, after smoothly passing through the second discharge pipes 55b, 55b extending upwardly to the roof 15.

[0079] With respect to Fig. 5B, the water drainage pipes 59, 59 are mounted to the connection blocks 56, 56. If water unfortunately flows from outside the roof 15 into the discharge pipes 54, 54, as shown by arrows ⑤, ⑤, the water passes downwardly into the water drainage pipes 59, 59 out of the exits 59b, 59b, as indicated by arrows ⑥, ⑥, ⑦, ⑦.

[0080] No water thus remains within the discharge pipes 54, 54. This leads to increased life of the discharge pipes 54, 54.

[0081] Discussion will be made as to how the forced ventilation structure 60 is operated in accordance with the present invention.

[0082] The spontaneous ventilation structure 50 is not suitable for advantageously discharging great amount of gaseous fuel leaked from the connection point.

[0083] In relation to Fig. 6A, if gaseous fuel remaining within the space 30a after leaking from the connection point has an amount exceeding the threshold level, the gas sensor 91 detects such gaseous fuel. The gas sensor 91 sends the control unit 92 a detection signal indicative of the detection of the gaseous fuel.

The control unit 92 transmits to the motor 76 of the fan 75 a drive signal for driving the motor 76.

[0084] Referring to Fig. 6B, upon receiving the drive signal, the motor 76 is driven to thereby rotate the blades 78, as shown
5 an arrow. Rotation of the blades 78 causes air within the first and second enlarged pipe portions 65b, 65c to be directed into the air introducing pipe 64, as shown by arrows ⑧, ⑨.

[0085] This causes the flap 70 to pivot clockwise from the closed position towards the opened position, as shown by an arrow

10 ⑨.

[0086] Turning to Fig. 7A, since the flap 70 is in the opened position, the opening 68b is opened. Air outside the automobile body 11 is drawn into the guide cylinder 73 via the intake pipe 72 of the intake portion 67, as indicated by an arrow ⑩. The
15 air is then taken into the air introducing pipe 64, as shown by arrows ⑪, ⑪, ⑪, ⑪.

[0087] Referring to Fig. 7B, after passing through the pipe 64, the air flows into the space 30a to thereby mix with the gaseous fuel which has leaked from the connection point, as indicated
20 by an arrow ⑫.

[0088] A mixture of the air and the gaseous fuel passes through the space 30a into the gas discharging pipe 80, as indicated by an arrow ⑬. The mixture flows through the pipe 80, as shown by an arrow ⑭.

25 [0089] The mixture is in part discharged out of the discharge pipes 54, 54. Because the discharge pipes 54, 54 are smaller in diameter than the gas discharging pipe 80, however, most of

the mixture flows into the pipe 80.

[0090] With respect to Fig. 8A, the mixture passes through the pipe 80 into the guide cylinder 88, as shown by an arrow ⑤, to thereby exert a wind pressure on the discharge flap 86. The flap 86 is thereby caused to pivot counterclockwise from the closed position to the opened position, as indicated by an arrow ⑥.

[0091] The counterclockwise pivotal movement of the flap 86 opens the opening 84b. After passing through the opening 84b, the mixture flows through the discharge port portion 89 and the exit 80b out of the right opening portion 33b, as shown by an arrow ⑦.

[0092] Reference is made to Fig. 9. It thus becomes possible to discharge the mixture out of the automobile body 11, as indicated by the arrow ⑦. By thus driving the fan 75, air outside the automobile body 11 is drawn or taken into the space 30a as shown by the arrows ⑩, ⑪ and mixes with the gaseous fuel to thereby provide the mixture. The mixture is therefore directed out of the automobile body 11, as shown by the arrows ⑬, ⑭.

[0093] By thus driving the fan 75, the gaseous fuel within the space 30a is forced to flow out of the automobile body 11 with efficiency.

[0094] The forced ventilation structure 60 thus arranged to force the gaseous fuel out of the automobile body 11 can be advantageously used in a fuel-cell-powered automobile employing hydrogen gas as gaseous fuel. It is to be understood that the forced ventilation structure may be used for advantageously discharging any gaseous fuel other than those described above.

[0095] By thus discharging most the gaseous fuel out of the automobile body 11, the gaseous fuel remaining within the space 30a decreases in amount to below the threshold level. The gas sensor 91 then ceases to detect the gaseous fuel within the space 30a. Thus, the control unit 92 is not supplied with any detection signal. Neither is the motor supplied with any drive signal, accordingly. The rotation of the blades 78 stops.

[0096] Thereafter, the intake flap 70 is returned to the closed position under its own weight to thereby close the opening 68b as shown in Fig. 3. Likewise, the discharge flap 86 is pivoted back to the closed position under its own weight to thereby close the opening 84b as shown in Fig. 4. It therefore becomes possible to prevent noise from being transmitted into the passenger compartment of the automobile 10. Further, it becomes possible to prevent unwanted foreign materials from entering into the air introducing pipe 64 and the gas discharging pipe 80.

[0097] The gaseous fuel discharging structure in the illustrated embodiment has been described as being used for discharging the gaseous fuel leaked from the connection point, however, it may be altered in such a manner as to discharge gaseous fuel leaked from within the tank body 41.

[0098] Material from which the flaps 70, 86 are made is not limited to rubber but includes other materials such as resin.

[0099] The fan 75 may be provided to the gas discharging pipe 80 rather than to the air introducing pipe 64. Furthermore, it is contemplated that both the air introducing pipe 64 and the gas discharging pipe 80 are provided with the fans 75, 75.

[0100] The present disclosure relates to the subject matter of Japanese Patent Application No. 2001-008313, filed January 16, 2001, the disclosure of which is expressly incorporated herein by reference in its entirety.

1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
2300
2301
2302
2303
2304
2305
2306
2307
2308
2309
2310
2311
2312
2313
2314
2315
2316
2317
2318
2319
2320
2321
2322
2323
2324
2325
2326
2327
2328
2329
2330
2331
2332
2333
2334
2335
2336
2337
2338
2339
2340
2341
2342
2343
2344
2345
2346
2347
2348
2349
2350
2351
2352
2353
2354
2355
2356
2357
2358
2359
2360
2361
2362
2363
2364
2365
2366
2367
2368
2369
2370
2371
2372
2373
2374
2375
2376
2377
2378
2379
2380
2381
2382
2383
2384
2385
2386
2387
2388
2389
2390
2391
2392
2393
2394
2395
2396
2397
2398
2399
2400
2401
2402
2403
2404
2405
2406
2407
2408
2409
2410
2411
2412
2413
2414
2415
2416
2417
2418
2419
2420
2421
2422
2423
2424
2425
2426
2427
2428
2429
2430
2431
2432
2433
2434
2435
2436
2437
2438
2439
2440
2441
2442
2443
2444
2445
2446
2447
2448
2449
2450
2451
2452
2453
2454
2455
2456
2457
2458
2459
2460
2461
2462
2463
2464
2465
2466
2467
2468
2469
2470
2471
2472
2473
2474
2475
2476
2477
2478
2479
2480
2481
2482
2483
2484
2485
2486
2487
2488
2489
2490
2491
2492
2493
2494
2495
2496
2497
2498
2499
2500
2501
2502
2503
2504
2505
2506
2507
2508
2509
2510
2511
2512
2513
2514
2515
2516
2517
2518
2519
2520
2521
2522
2523
2524
2525
2526
2527
2528
2529
2530
2531
2532
2533
2534
2535
2536
2537
2538
2539
2540
2541
2542
2543
2544
2545
2546
2547
2548
2549
2550
2551
2552
2553
2554
2555
2556
2557
2558
2559
2560
2561
2562
2563
2564
2565
2566
2567
2568
2569
2570
2571
2572
2573
2574
2575
2576
2577
2578
2579
2580
2581
2582
2583
2584
2585
2586
2587
2588
2589
2590
2591
2592
2593
2594
2595
2596
2597
2598
2599
2600
2601
2602
2603
2604
2605
2606
2607
2608
2609
2610
2611
2612
2613
2614
2615
2616
2617
2618
2619
2620
2621
2622
2623
2624
2625
2626
2627
2628
2629
2630
2631
2632
2633
2634
2635
2636
2637
2638
2639
2640
2641
2642
2643
2644
2645
2646
2647
2648
2649
2650
2651
2652
2653
2654
2655
2656
2657
2658
2659
2660
2661
2662
2663
2664
2665
2666
2667
2668
2669
2670
2671
2672
2673
2674
2675
2676
2677
2678
2679
2680
2681
2682
2683
2684
2685
2686
2687
2688
2689
2690
2691
2692
2693
2694
2695
2696
2697
2698
2699
2700
2701
2702
2703
2704
2705
2706
2707
2708
2709
2710
2711
2712
2713
2714
2715
2716
2717
2718
2719
2720
2721
2722
2723
2724
2725
2726
2727
2728
2729
2730
2731
2732
2733
2734
2735
2736
2737
2738
2739
2740
2741
2742
2743
2744
2745
2746
2747
2748
2749
2750
2751
2752
2753
2754
2755
2756
2757
2758
2759
2760
2761
2762
2763
2764
2765
2766
2767
2768
2769
2770
2771
2772
2773
2774
2775
2776
2777
2778
2779
2780
2781
2782
2783
2784
2785
2786
2787
2788
2789
2790
2791
2792
2793
2794
2795
2796
2797
2798
2799
2800
2801
2802
2803
2804
2805
2806
2807
2808
2809
2810
2811
2812
2813
2814
2815
2816
2817
2818
2819
2820
2821
2822
2823
2824
2825
2826
2827
2828
2829
2830
2831
2832
2833
2834
2835
2836
2837
2838
2839
2840
2841
2842
2843
2844
2845
2846
2847
2848
2849
2850
2851
2852
2853
2854
2855
2856
2857
2858
2859
2860
2861
2862
2863
2864
2865
2866
2867
2868
2869
2870
2871
2872
2873
2874
2875
2876
2877
2878
2879
2880
2881
2882
2883
2884
2885
2886
2887
2888
2889
2890
2891
2892
2893
2894
2895
2896
2897
2898
2899
2900
2901
2902
2903
2904
2905
2906
2907
2908
2909
2910
2911
2912
2913
2914
2915
2916
2917
2918
2919
2920
2921
2922
2923
2924
2925
2926
2927
2928
2929
2930
2931
2932
2933
2934
2935
2936
2937
2938
2939
2940
2941
2942
2943
2944
2945
2946
2947
2948
2949
2950
2951
2952
2953
2954
2955
2956
2957
2958
2959
2960
2961
2962
2963
2964
2965
2966
2967
2968
2969
2970
2971
2972
2973
2974
2975
2976
2977
2978
2979
2980
2981
2982
2983
2984
2985
2986
2987
2988
2989
2990
2991
2992
2993
2994
2995
2996
2997
2998
2999
3000
3001
3002
3003
3004
3005
3006
3007
3008
3009
3010
3011
3012
3013
3014
3015
3016
3017
3018
3019
3020
3021
3022
3023
3024
3025
3026
3027
3028
3029
3030
3031
3032
3033
3034
3035
3036
3037
3038